

## Reducing Tee 130R

### Product Description

#### Product Certification

UL Listed / FM Approved (EX 6624)

#### Material

ASTM A536

#### Threads

ASME B1.20.1

#### Pressure Rating

Test Pressure : 12.5 MPa

Max. Working Pressure : 2.5 MPa



### Dimensions (in mm)

| Inch              | mm       | A    | B    | C    |
|-------------------|----------|------|------|------|
| 1×1/2×1           | 25x15x25 | 38.1 | 38.1 | 35.5 |
| 1×3/4×1           | 25x20x25 | 38.1 | 38.1 | 36.8 |
| 1.1/4×1/2×1.1/4   | 32x15x32 | 44.5 | 44.5 | 38.9 |
| 1.1/4×1×1.1/4     | 32x25x32 | 44.5 | 44.5 | 42.4 |
| 1.1/2×1×1.1/2     | 40x25x40 | 49.3 | 49.3 | 45.7 |
| 1.1/2×1.1/4×1.1/2 | 40x32x40 | 49.3 | 49.3 | 47.8 |
| 2×1×2             | 50x25x50 | 57.2 | 57.2 | 51.3 |
| 2×1.1/4×2         | 50x32x50 | 57.2 | 57.2 | 53.3 |
| 2×1.1/2×2         | 50x40x50 | 57.2 | 57.2 | 54.8 |

